

Vanguard VIS 8532-PH-IV 4.0 MP Pinhole Camera

WDR Full HD ATM Camera



Features

- H.265 & H.264 triple-stream encoding
- Support Smart H.265+/H.264+
- 50/60fps@1080P (1920×1080)
- Day/Night (Electronic), WDR, 3DNR, AWB, AGC, BLC
- Smart detection
- Micro SD memory, PoE
- Multiple Lens Unit optional

Vanguard VIS 8532-PH-IV

Camera	
Image Sensor	1/3" 4.0 Megapixel Progressive scan CMOS
Effective Pixels	1920(H) x 1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s
Min. Illumination	Color: 0.001Lux/F2.8 Color B/W: 0.0002Lux/F2.8
S/N Ratio	More than 50dB
Camera Features	
WDR range	120dB
Day/Night	Auto /Color/ B/W
Backlight Compensation	BLC / HLC / WDR
White Balance	Auto/Manual/Sunny/Night /Outdoor /Customized
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm
Max Aperture	F2.8
Focus Control	Manual
Video	
Compression	H.265+/H.265H/H.264+/H.264
Resolution	1080P(1920x1080)/720P(1280x720)/ D1 (704x576), 2CIF(704x240) /CIF (352x288)
Frame Rate	Up to 20 Streams 1080P (1-25/30fps) for Live Viewing and Recording at Native Resolutions Other: D1/CIF (1-25/30fps)
	Sub Stream D1/2CIF/ CIF (1 ~ 25/30fps)
	Third Stream 1080P (1 ~ 25/30fps)
Bit Rate	H.265: 14Kbps~ 5630Mbps/ H.264: 24Kbps~ 9472Mbps
ATM Text Integration	
Integration Type	Dynamic Secure Integration
Variable Fields	4
Search for Video	Date/Time/Text

Smart Function	
Smart detection	Tripwire
	Intrusion
	Scene change
	Missing/Abandoned
	Bandwidth Management
	Text Integration
	ANR (Automatic Network Recovery)
Face detect	
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS Band width Management ,Text Integration, ANR, Bonjour
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 256 GB supporting ANR
Alarm	2/2 channel In/Out
General	
Power Supply	DC12V / PoE (802.3af)
Power Consumption	<5W
Working Environment	-30°C~+70°C, Less than 95% RH
Dimensions	109.7mm× 82.8mm× 24.0mm 47mm x26mm
Weight	0.4Kg
Warranty	Vanguard 1-year warranty and Vanguard Extended Warranty option